



Cotton Sash Cord Specifications & Technical Data

Manufactured from natural unbleached 100% cotton fiber grown and spun in the USA and manufactured into rope in Canada.

Diameter	Weight (lb/100')	MBS	Available Packages	PART #
4mm (5/32")	0.5lb	95lbf	100ft / 10lb (2,200') Reel	01-050
5mm (3/16")	0.7lb	120lbf	100ft / 10lb (1,385') Reel	01-060
5.5mm (7/32")	0.8lb	200lbf	100ft / 10lb (1,275') Reel	01-070
6mm (1/4")	1.0lb	200lbf	100ft / 10lb (1,030') Reel	01-080
7mm (9/32")	2.0lb	275lbf	100ft / 10lb (750') Reel	01-090
8mm (5/16")	2.0lb	600lbf	100ft / 10lb (500') Reel	01-100
10mm (3/8")	2.6lb	610lbf	100ft / 10lb (380') Reel	01-120
11mm (7/16")	3.2lb	720lbf	100ft / 10lb (310') Reel	01-140
13mm (1/2")	4.1lb	925lbf	100ft / 10lb (245') Reel	01-160

*Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

Applications

- Movie & theatre production
- Industrial
- Crafting

Features

- Soft feel for excellent handling
- Non-rotating torque free design
- Excellent knotting

Fiber Specifications

- Strength easily compromised
- Deteriorates in moisture; susceptible to mildew
- Chars at 148°C

Specifications may change without notice. We recommend referring to cancord.com for the most up to date information, or requesting a current specification sheet when ordering.



Revision 2024-08