



Military Cord Specifications & Technical Data

Manufactured from spun polyester fiber to specification D-80-01-028/SF-001 & DSPM 2-2-80-028.

Diameter	Weight (lb/100')	MBS	Colour	NSN	Available Packages	PART #
3mm (7/64")	0.3lb	170lbf	Olive Drab	4020-21-882-9701	250m tube	16-111-62
3mm (7/64")	0.3lb	170lbf	Black	4020-21-882-9715	250m tube	16-111-62B
3mm (7/64")	0.3lb	170lbf	White	4020-21-882-9680	250m tube	17-111-62
5mm (3/16")	0.7lb	400lbf	Olive Drab	4020-21-874-2586	250m tube	16-222-62
5mm (3/16")	0.7lb	400lbf	Black		250m tube	16-222-62B
5mm (3/16")	0.7lb	400lbf	White	4020-21-106-1391	250m tube	17-222-62

*Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

Applications

- Military gear & equipment
- General use
- Lashing

Features

- Soft feel for excellent handling
- Non-rotating torque free
- Excellent knotting

Fiber Specifications

- Excellent microbial resistance
- Durability
- Melts at 254°C

Specifications may change without notice. We recommend referring to cancord.com for the most up to date information, or requesting a current specification sheet when ordering.



Revision 2024-09