

## Nautical Rescue / Nautical Throw Rope Specifications & Technical Data

Manufactured from high tenacity MFP for water rescue applications.

| Diameter | Weight<br>(lb/100') | MBS      | Elongation<br>(at 10% of<br>MBS) | Colour     | Available<br>Packages | PART#  |
|----------|---------------------|----------|----------------------------------|------------|-----------------------|--------|
| 8mm      | 2.3lb               | 2,000lbf | 1.5%                             | Yellow/Red | 600' / 1,200'         | 07-308 |
| 10mm     | 3.5lb               | 3,500lbf | 3%                               | Yellow/Red | 600' / 1,200'         | 07-610 |
| 12.7mm   | 5lb                 | 4,000lbf | 3%                               | Yellow/Red | 600' / 1,200'         | 07-613 |

<sup>\*</sup>Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

## **Applications**

- Throw Bags
- Life Rings
- Water Rescue

## **Features**

- Floats
- Light weight
- High visibility

## **Fiber Specifications**

- Unaffected by water
- Excellent microbial resistance
- Melts at 165°C

Specifications may change without notice. We recommend referring to cancord.com for the most up to date information, or requesting a current specification sheet when ordering.





Revision 2025-03